

Armafinish® 99

THE ELASTIC PAINT DESIGNED FOR
PROTECTION AND COVERING OF
ARMAFLEX®



- Resistant to weathering and ageing. Coating remains elastic
- Drip-free paint
- Protection of Armaflex® insulation materials

Technical Data - Armafinish 99

Brief description	Armafinish 99 is a UV resistant paint that remains permanently elastic, is resistant to weathering and has good ageing resistance.
Material type	Non-drip
Colour	white (RAL 9001) or grey (RAL 7037)
Material Special Information	Normal consumption: 0.55 litres per m ² when two coats are applied (corresponds to a dry film thickness of 0.26mm).
Applications	Protection of Armaflex insulation materials when installed outdoors and for marking purposes when used indoors.
Assembly	All Armaflex insulation except HT/Armaflex and Armaflex Ultima (see relevant product data sheet) that is installed outdoors should be covered with two complete coats of Armafinish 99. Application temperature: + 10 °C to + 30 °C, maximum relative humidity 80%. Drying time at + 20 °C: approx. 2 hours. It is also necessary to allow 2 hours inbetween coats and the second coat must be applied within 7 days. Paint may be applied using a brush or roller. Clean tools with water.
Remarks	Unprotected Armaflex must not be exposed to weathering for more than 3 days and Armafinish 99 paint should be applied as soon as possible. The protective coating should be inspected at regular intervals. After 2 years at the latest, two further coats should be applied. Refer to special instruction / safety data sheet.

Property	Value/Assessment	Special Remarks
Other technical features		
Storage & Shelf life	Shelf-life in unopened container: 12 months.	Keep container tightly closed and store in a cool, well ventilated and frost-free place.
Explosion limits	Lower: none Upper: none	
Hazard Class	Environmentally hazardous substance as defined by the transport regulations (ADR/RID, IMDG-Code, ICAO-TI/IATA-DGR).	
Recycling	Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company. More details see relevant Safety Data Sheet.	Can must be emptied prior to recycling. Cans containing adhesive must be recycled into new products.

All statements and technical information are based on results obtained under typical conditions. It is the responsibility of the recipient to verify with us that the information is appropriate for the specific use intended. Installation instructions are given in our Armaflex installation manual.

Armacell UK Ltd

Mars Street • Oldham • OL9 6LY • Lancashire • United Kingdom
Phone +44 (0)161 287 7000 • Fax +44 (0)161 633 2685
www.armacell.co.uk • info.uk@armacell.com

IPRP-0039-170111-en(GB)



armacell[®]

© 2019 Armacell Enterprise GmbH & Co. KG. Subject to alterations without prior notice. Our general conditions of sales & delivery shall apply.