



NOTES

FEATURES AND BENEFITS

- CAN BE ADAPTED TO FIT ALL OTHER PIPEWORK SYSTEMS
- QUICK AND SIMPLE TO INSTALL
- ACCESS SHAFTS CAN BE EASILY CUT ONSITE TO REQUIRED DEPTH
- GRANULAR BACKFILL - SEE ENVIRO TURTLE INSTALLATION INSTRUCTIONS

COMPLIANCE

- CHAMBERS COMPLY TO EN13598 - 2 (2010)
- NON- MAN - ENTRY INSPECTION CHAMBERS COMPLY TO SFA7 TYPE 4 SPECIFICATION TO MAXIMUM DEPTH OS 2000mm
- BUILDING REGULATIONS - PART H1 TO A MAXIMUM DEPTH OF 600mm

APPLICATION

- ABOVE GROUND ACCESS FOR INSPECTION AND MAINTENANCE OF SURFACE WATER PIPEWORK SYSTEMS
- DESIGNED FOR USE IN BOTH FOUL AND SURFACE WATER DRAINAGE SYSTEMS
- SUITABLE FOR ADOPTABLE AND NON-ADOPTABLE APPLICATIONS
- MAXIMUM INSTALLATION DEPTH - ADOPTABLE AND NON-ADOPTABLE 2000mm



DRAWN BY:-	R.U.	CONTRACT REFERENCE:-		N/A
DRAWN DATE:-	10/09/2019	PRODUCT DESCRIPTION		
		600 INSPECTION CHAMBER 1500mm		
APPROVED	D.A.	SIZE	PRODUCT CODE	REV
		A3	AIC16060015SP	2
		SCALE	1:7.5	SHEET 1 OF 1