

# Kingspan Ferham Specification sheet Low Level cisterns (Coffin)

## Features

- Application - Storage and supply of cold potable water to an open vented cylinder, or use as expansion tanks in vented heating systems
- Roto-moulded from approved hygienic polypropylene plastic
- Manufactured to BS4213:2004, using WRAS approved materials
- Supplied with close fitting lid, 22mm Byelaw 30 fittings, backing plate, 60mm insulation jacket and ties
- 1-Year Guarantee against manufacturing defects



Capacity		Height (mm)	Width (mm)	Depth (mm)	Code CISTERN
G	L				
25	114	395	1120	490	<a href="#">FC25GL</a>
40	182	495	1562	457	<a href="#">FC40GL</a>
50	227	490	1420	530	<a href="#">FC50GL</a>
100	455	590	1790	644	<a href="#">FC100GL</a>

Note: As Kingspan maintains a policy of ongoing continuous improvement, these specifications are subject to change without notice.

GB Sales Office:  
T. 0345 260 0258  
E. [cylinder.sales@kingspan.com](mailto:cylinder.sales@kingspan.com)

Technical Support:  
T. 0345 260 0007  
E. [cylinder.tech-support@kingspan.com](mailto:cylinder.tech-support@kingspan.com)

Wakefield Office:  
Kingspan Water & Energy Ltd.  
Tadman Street, Wakefield,  
West Yorkshire, WF1 5QU

NI Sales Office:  
T: 028 3836 4520  
E: [cylindersinfo@kingspan.com](mailto:cylindersinfo@kingspan.com)

Customer Services:  
T. 0345 260 7260  
E. [customer care@kingspan.com](mailto:customer care@kingspan.com)